

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Flex Tint for Capture Stain  
 Product code : Chestnut, Mahogany

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Colorant Concentrate to be added to Capture Stain

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the OSHA requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, MSDS or both in accordance with applicable government regulations.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Sashco, Inc.  
 10300 E. 107th Place  
 Brighton, CO 80601 - USA  
 T 800.767.5656  
[info@sashco.com](mailto:info@sashco.com)

##### Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada

#### 1.4. Emergency telephone number

Emergency number : 800.535.5053

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Skin Sens. 1B  
 Carc. 2

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



GHS07

GHS08

Signal word (GHS) :

Warning

Hazard statements (GHS) :

May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

# Flex Tint for Capture Stain

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 3.2. Mixtures

Name	Product identifier	%
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )	(CAS-No.) 1309-37-1	9 - 20
Carbon black	(CAS-No.) 1333-86-4	2.1 – 3.4
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	(CAS-No.) 126-86-3	0.46 - 1

\* The concentrations listed represent actual ranges that result from batch variability.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

### 5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
-----------------	---

# Flex Tint for Capture Stain

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Spilled material may present a slipping hazard.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Formaldehyde and ethylene oxide are subject to the standards 29 CFR 1910.1048 and 1910.1047, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.

Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Flex Tint for Capture Stain</b>	
No additional information available	
<b>Iron oxide (Fe<sub>2</sub>O<sub>3</sub>) (1309-37-1)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Iron oxide fume
OSHA PEL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume) 15 mg/m <sup>3</sup> (total dust (Rouge)) 5 mg/m <sup>3</sup> (respirable fraction (Rouge))
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
US IDLH (mg/m <sup>3</sup> )	2500 mg/m <sup>3</sup> (dust and fume)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (dust and fume)
<b>5-Decyne-4,7-diol, 2,4,7,9-tetramethyl- (126-86-3)</b>	
No additional information available	
<b>Carbon black (1333-86-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Carbon black
ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
Remark (ACGIH)	TLV@ Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Carbon black
OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> (Carbon black in presence of Polycyclic aromatic hydrocarbons)

# Flex Tint for Capture Stain

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. Provide readily accessible eye wash stations and safety showers.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment. Maintain levels below Community environmental protection thresholds.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Brown/Grey to Black
Odour	: Mild.
Odour threshold	: No data available
pH	: 8 – 9
Melting point	: No data available
Freezing point	: 0 °C / 32 °F
Boiling point	: 100 °C / 212 °F
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C (68 °F)	: No data available
Relative density	: 10.4 – 10.5
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 3000 cP
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat.

# Flex Tint for Capture Stain

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

#### 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl- (126-86-3)

LD50 oral rat	> 500 mg/kg
LD50 dermal rabbit	> 1000 mg/kg
LC50 inhalation rat	> 20 mg/l (Exposure time: 1 h)

#### Carbon black (1333-86-4)

LD50 oral rat	> 15400 mg/kg
---------------	---------------

Skin corrosion/irritation : Not classified.  
pH: 8 – 9  
Serious eye damage/irritation : Not classified.  
pH: 8 – 9  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Suspected of causing cancer.

#### Iron oxide (Fe2O3) (1309-37-1)

IARC group	3 - Not classifiable
------------	----------------------

#### Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified.  
STOT-single exposure : Not classified.  
STOT-repeated exposure : Not classified.  
Aspiration hazard : Not classified.  
Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.  
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Chronic symptoms : Suspected of causing cancer.  
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# Flex Tint for Capture Stain

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Recycle empty containers where allowed.

Additional information : Empty containers may contain residues which are hazardous.

## SECTION 14: Transport information

### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

## SECTION 15: Regulatory information

### 15.1. Federal regulations

No additional information available

### 15.2. International regulations

No additional information available

### 15.3. US State regulations


**⚠ WARNING:** Cancer and Reproductive harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16: Other information

Revision date : 12/10/2020  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



NFPA health hazard : 2  
NFPA fire hazard : 0  
NFPA reactivity : 0



Hazard Rating  
Health : 2 Moderate Hazard  
\*  
Flammability : 0 Minimal Hazard  
Physical : 0 Minimal Hazard

SDS HazCom 2012 - WHMIS 2015 (NexReg)

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*