

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Transformation Log Neutral Base for Flex Tint
 Product code : 67355

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Coating, Stain Base, untinted
 Recommended use : Consumer use, Industrial use

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the OSHA/WHMIS requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, MSDS or both in accordance with applicable government regulations.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Sashco, Inc.
 10300 E. 107th Place
 Brighton, CO 80601 - USA
 T 800.767.5656
info@sashco.com

Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada

1.4. Emergency telephone number

Emergency number : 800.535.5053

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 3
 Carc. 2
 Repr. 2

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS08

Signal word (GHS) :

Warning

Hazard statements (GHS) :

Flammable liquid and vapour. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Stoddard solvent	(CAS-No.) 8052-41-3	10 – 30
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	0.1 - 1
Hexanoic acid, 2-ethyl-, zirconium salt (1:?)	(CAS-No.) 22464-99-9	0.1 - 1
Ethylbenzene	(CAS-No.) 100-41-4	0.1 - 1
Isopropylbenzene	(CAS-No.) 98-82-8	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash clothing before re-using. Get medical attention if irritation develops and persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water fog. Carbon dioxide (CO ₂). Dry chemical. Foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. Products of combustion may include, and are not limited to: oxides of carbon. Material will oxidize and can cause SPONTANEOUS COMBUSTION of contaminated rags, sawdust, or other ignitable absorbent material. Immerse in water immediately.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.
------------------	---

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment. Contaminated rags or other ignitable absorbent material used in clean up should be laid flat to dry completely before disposal or immersed in water immediately to prevent spontaneous combustion.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with eyes, skin and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only non-sparking tools. Stir well before use. Wear personal protective equipment. Lead is subject to the standard 29 CFR 1910.1025, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Transformation Log Neutral Base for Flex Tint	
No additional information available	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA [1]	435 mg/m ³
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

USA - ACGIH - Biological Exposure Indices	
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl benzene
OSHA PEL TWA [1]	435 mg/m ³
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1 OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	435 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL STEL	545 mg/m ³
NIOSH REL STEL [ppm]	125 ppm
Hexanoic acid, 2-ethyl-, zirconium salt (1:?) (22464-99-9)	
No additional information available	
Isopropylbenzene (98-82-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Cumene
ACGIH OEL TWA [ppm]	50 ppm
Remark (ACGIH)	TLV® Basis: Eye, skin, & URT irr; CNS impair
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Cumene
OSHA PEL TWA [1]	245 mg/m ³
OSHA PEL TWA [2]	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	900 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	245 mg/m ³
NIOSH REL TWA [ppm]	50 ppm
US-NIOSH chemical category	Potential for dermal absorption
Stoddard solvent (8052-41-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Stoddard solvent
ACGIH OEL TWA [ppm]	100 ppm
Remark (ACGIH)	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Stoddard solvent
OSHA PEL TWA [1]	2900 mg/m ³
OSHA PEL TWA [2]	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	20000 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	350 mg/m ³
NIOSH REL C	1800 mg/m ³

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use explosion-proof equipment. Provide readily accessible eye wash stations and safety showers.
Hand protection	: Wear suitable gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Translucent yellow liquid
Colour	: Yellow
Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 40.556 °C (105 °F) [Pensky-Martins CC]
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C (68 °F)	: No data available
Relative density	: No data available
Density	: 8.7 lb/gal / 1.0 kg/l
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 50 cSt
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

May form flammable/explosive vapour-air mixture. Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Material will oxidize and can cause SPONTANEOUS COMBUSTION of contaminated rags, sawdust, or other ignitable absorbent material. Immerse in water immediately.

10.4. Conditions to avoid

Keep away from heat, sparks, and flame. Sources of ignition. Direct sunlight. Incompatible materials.

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (vapours)	11 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	15400 mg/kg bodyweight
ATE CA (vapours)	17.4 mg/l/4h

Isopropylbenzene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 µl/kg
LC50 inhalation rat	> 3577 ppm (Exposure time: 6 h)
ATE CA (oral)	1400 mg/kg bodyweight
ATE CA (Dermal)	12300 mg/kg bodyweight

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Suspected of causing cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Isopropylbenzene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified.

Aspiration hazard : Not classified.

Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Transformation Log Neutral Base for Flex Tint

Viscosity, kinematic (calculated value) (40 °C) : 50 mm²/s

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No additional information available.

12.3. Bioaccumulative potential

No additional information available.

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint related material
Class (DOT) : Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III
Hazard labels (DOT) :



Transportation of Dangerous Goods (TDG)

In accordance with TDG

UN-No. (TDG) : UN1263
Proper Shipping Name (TDG) : PAINT RELATED MATERIAL
TDG Primary Hazard Classes : Class 3 - Flammable Liquids
Packing group (TDG) : III
Hazard labels (TDG) :



Transformation Log Neutral Base for Flex Tint

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 15: Regulatory information

15.1. Federal regulations

No additional information available.

15.2. International regulations

No additional information available

15.3. US State regulations


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 02/17/2021
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



NFPA health hazard : 0
NFPA fire hazard : 2
NFPA reactivity : 0



Hazard Rating
Health : 0 Minimal Hazard
*
Flammability : 2 Moderate Hazard
Physical : 0 Minimal Hazard

SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.