

The Tough Elastic Sealant for Every Job

LEXEL[®]

Sticks to Almost Anything*



DESCRIPTION:

Super-elastic. Superior adhesion. Paintable. It seals around anything: tubs and shower stalls, sinks and counter tops, window frames and door frames, PVC and metal pipes. Apply to wet or dry surfaces, indoors and outdoors. It's tough and can handle up to 800% joint movement. It's scrubbable. It sticks to just about anything. Lexel clear sealant is 19 times clearer than silicone and won't yellow or cloud up over time. Lexel won't let you down.

WHERE TO USE:

- In most any place you'd use silicone, including:
- Kitchens and bathrooms, including fixtures, countertops and backsplashes
 - On wallpaper edges to prevent curling
 - Around trim, windows, doors, thresholds, sills, siding, vents, pipes and air conditioners
 - Around leaky duct work

***ADHERES TO:** (all conform to ASTM C794)

Most building materials including:

Metals

- Aluminum
- Brass
- Steel
- Copper
- Silver

Plastics

- ABS
- Vinyl
- Nylon
- PVC
- Fiberglass
- Acrylic Sheet
- Plexiglass
- Lexan[®]**
- Nylon
- Polycarbonate

OTHER SURFACES:

- Asphalt
- Concrete
- Glass
- Wood
- Corian[®]**
- Cement
- Thinset
- Stone
- Drywall
- Stucco
- EIFS
- Brick
- Mortar
- Ceramic Tile
- Formica[®]**
- Fiber Cement
- Alkyd Stain
- Cloth/Canvas
- Porcelain

COLORS:

- Clear
- White (White not available in CA)
- White Lower VOC

(Lexel White Lower VOC is required in these states: CT, DE, DC, IL, IN, ME, MD, MA, MI, NH, OH, NJ, NY, PA, RI, VT, VA, UT.)

PACKAGING:

- 10.5 oz. plastic cartridges
- 5 oz. squeeze tubes

COVERAGE:

A 10.5 oz. cartridge will yield approx. 26 lineal feet with a 1/4" (6 mm) bead.

PAINTABILITY:

With latex paint/stain after 24-48 hours or oil-based paint/stain after 3-4 weeks

** Corian[®], Lexan[®] and Formica[®] are registered trademarks of their respective owners.

FEATURES

- 19 times clearer than silicone
- Super elastic with strong adhesion, won't tear, crack or pull away
- Paintable
- Water & mildew-resistant
- Won't freeze
- Use on wet or dry surfaces
- Tough & easily cleaned
- Limited Lifetime Warranty
- Exclusive stop flow plunger
- High durability
- Full 10.5 oz. in every cartridge

BENEFITS

- No cloudiness or ugly caulk lines
- Eliminates costly call backs
- Unlike silicone, paint sticks with no separation
- Use indoors or outdoors
- No wasted caulk in cold weather
- Apply in most any weather
- Clean with abrasive cleaners with no damage
- Have confidence that you're using the right product
- Less waste, less mess
- Performs well in most any type of climate
- More for your money

WHERE NOT TO USE:

- Areas of submersion where there is animal life (i.e. aquariums)
- With polystyrene insulation
- Containment applications
- Plastics not listed should be tested for compatibility before use
- Will not adhere to or is incompatible with Aquaseal[®], cultured marble, Kynar[®], polypropylene, polystyrene foam insulation, polyethylene, rubber, silicone, styrofoam (it dissolves it), vulcanized rubber, waxes

APPLICATION:

- Large beads applied in hot weather (above 95°F) may exhibit slight bubbling. For best results, apply out of direct sunlight.
- Prepare frosty or icy surfaces by cleaning with alcohol.
- If using indoors, make sure the room is well-ventilated.
- Natural shrinkage may give some joints a concave appearance. Multiple applications may be needed to fill the joint flat.
- If dirt or oils are present on the substrate, wash with any household cleaner, rinse to remove and allow to thoroughly dry.
- Remove any old caulk, especially silicone or silicone residue. Use a silicone remover.
- Insert backer rod into joints deeper than 1/2" to provide for proper sealant depth and a stronger, longer lasting seal.

Cartridge:

- Gun Lexel into the joint with a caulk gun.

Squeeze Tube:

- Squeeze Lexel into the joint.
- Tool for a smoother bead using a caulking tool or a soapy finger and a light, skimming touch.

STORAGE AND CLEAN-UP:

- Clean tools with mineral spirits, paint thinner or citrus-based cleaners.
- Clean hands with citrus-based cleaners.
- Lexel cartridges can be stored if sealed tightly. Wrap cartridge nozzles tightly with plastic wrap and a rubber band.
- Lexel squeeze tubes can be stored by tightly replacing the cap.

TYPICAL PROPERTIES:

Property	Value
Joint Size	Maximum 2"
Clarity (NTU):	< 13
Radon Barrier:	Stops 94%
Application Range	0°F to 120°F (-18°C to 49°C) surface temperature
Service Range	-30°F to 200°F (-34°C to 93°C)
Freeze-Thaw Stability	Won't freeze
Tensile Properties	Recovery at 50% stretch: 96% in 1 min Recovery at 100% stretch: 96% in 1 min
VOC	Clear: 380 g/L, 43% by wt. White: 382 g/L, 44% by wt. (Clear is VOC exempt in 49 states and Canada) White Lower VOC: 40.7 g/L, 4% by wt.

TEST DATA:

Property	Results	Test Method
Durability	25% total joint movement (10 cycles @ -15°F (-26°C))	ASTM C719
Hardness, Shore A	25 (21-day cure)	ASTM C661
Slump	< 1/8"	ASTM D2202
Solids	55.9% by weight	ASTM C1250
Extrusion Rate	80 g/min (1/8" orifice at 40 psi)	ASTM C603
Cured	1 week (dependent on temperature, humidity and bead size/thickness)	ASTM C679
Tack-free	Less than 30 minutes	ASTM C679
Low Temp. Flexibility	Pass (not artificially weathered)	ASTM C734
Adhesion-in-peel Passing Substrates	See "ADHERES TO" section on front page	ASTM C794

SPECIFICATIONS:

- Meets FHA requirements.

The data reported here are believed to be reliable. No warranty is made concerning the accuracy of or the results obtained from their use.

* Aquaseal[®] and Kynar[®] are registered trademarks of their respective owners.

DANGER: VAPOR HARMFUL. FLAMMABLE. EYE & SKIN IRRITANT. Do not swallow. Do not breathe fumes. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin or clothing. KEEP OUT OF REACH OF CHILDREN. Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area.

Contains toluene.

FIRST AID: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

⚠ WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

LIMITED LIFETIME WARRANTY: Sashco warrants this product will substantially meet published specifications on the date of sale. If it fails to do so, return unused portion with original sales receipt for replacement or refund, at Sashco's sole option. These are purchaser's sole and exclusive remedies for any breach of warranty. Purchaser must determine suitability of product for purchaser's specific needs and assumes all risk associated with its use. Sashco will not be liable for direct or indirect damages.

For a detailed description of the warranty & exclusions, visit www.sashco.com.



10300 E. 107th Pl., Brighton, CO 80601
800-767-5656 • www.sashco.com

Made in the USA

Follow Sashcoinc on:

