

NANO™

PENETRATING WOOD SEALER

— protects against —
WATER / MOLD / DECAY

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

SEAL-ONCE® NANO Penetrating Wood Sealer protects and stabilizes wood against water damage and decay. The water based formula uses proprietary nanotechnology to form a flexible breathable barrier by coating the wood fibers at the cellular level.

NANO allows wood to age naturally without decay, and can be used to preserve old or new wood, extending its natural life. It is non-film forming and will not alter the natural beauty of the wood.

NANO preserves the integrity of the wood by inhibiting rot, mold and mildew growth, and helps to eliminate warping and cupping. Nano forms a flexible breathable barrier that allows the wood to expand and contract, and for water vapor to escape.

The advanced technology of NANO allows it to penetrate and bond to the cellular structure of the wood, forming a superior barrier below the surface to protect from the inside out.

NANO goes on milky white and dries clear. It is also available in semi-transparent tints.

RECOMMENDED APPLICATIONS

Designed to be used on unfinished interior and exterior wood surfaces including:

- Log Homes
- Wood siding
- Fences
- Thermally Modified
- Outdoor furniture
- Swing Sets
- Pergola
- Shakes
- Decks

FEATURES

- Eco-friendly
- Non-toxic; will not harm pets, plants or people
- Ultra-low VOC
- Water based formula
- Non-film forming, flexible, breathable barrier
- Will not peel
- Helps to resist warping, cupping, wood rot & decay
- Helps to resist mold & mildew growth
- Soap & water cleanup
- Enhances natural grain of the wood
- Tinted formula provides additional UV protection

PHYSICAL CHARACTERISTICS

Color	Milky white liquid, dries clear
Flash Point	None
pH	7+
Solvents	Water
lbs/gal	8.4
Specific Gravity	1.007
Viscosity	3.2 cps
Application Temp.	45°F/7.22°C* - 95°F/35°C
Odor	Nil
VOC Content	28g/L**

*Do not apply when air or surface temperature is below 45°F/7.22°C or may fall below 45°F/7.22°C within 24 hours after application.

**VOC Content determined via EPA Method 24.

PACKAGING SIZES

1 Quart Can | 1 Gallon Can | 5 Gallon Pail | 55 Gallon Drum

FREIGHT CLASS

55



NANO™

PENETRATING WOOD SEALER

— protects against —
WATER / MOLD / DECAY

APPLICATION INSTRUCTIONS

PREPARATION

- All surfaces should be cleaned before sealing for best penetration and performance. Remove all old coatings, dust, debris and loose material. Remove oil, grease, algae, grime, mill glaze and mold and mildew stains with appropriate cleaners. Recommend SEAL-ONCE All Wood Cleaner.
- After cleaning, test absorbency of surface by sprinkling a few drops of water on the surface. If the water does not readily penetrate the surface, stripping will be necessary to remove old coatings prior to applying SEAL-ONCE NANO Penetrating Wood Sealer. Retest surface when dry.

APPLICATION

- Do not use if air or surface temperature is below 45°F/7.22°C or above 95°F/35°C.
- Do not apply in rain or when rain is expected within 12-24 hours.
- DO NOT THIN. Mix well. Stir contents or shake thoroughly prior to use.
- Test a small area to ensure acceptable appearance and penetration.
- Apply first coat with a synthetic brush; pump-up garden sprayer; air-assisted; and/or airless sprayer. Use 15-17 tip and medium to coarse spray pattern. When spraying, always back brush for best results.
- Second coat can be applied once first coat has penetrated but is still damp. Second coat must be applied within one hour of applying first coat.
- For best results, apply in the shade and out of direct sunlight.
- When applying in direct sunlight and wood surface is hot, spray with a mist of water and apply NANO immediately on dampened surface.
- Apply to all surfaces. Apply SEAL ENDS ONCE® to wood ends.
- Do not use with other waterproofing products.

COVERAGE

- Approximate coverage: 250-350 sq. ft./gallon per coat. Actual coverage may vary due to the porosity of the substrate.

DRYING TIME

- Allow approximately 2-3 hours for surface to dry, depending on temperature and humidity.
- Allow 12-24 hours for full cure, depending on temperature and humidity.
- When recoating, apply once previous coat has penetrated and surface is damp, not wet. Second coat must be applied within one hour of applying the first coat.

CLEANUP AND STORAGE

- Clean all application equipment with warm soapy water.
- Store above 32°F/0°C to protect from freezing.
- Shelf life (unopened): 3 years
- Disposal: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

PRECAUTIONS

- Protect adjacent areas from overspray and runoff, including windows and siding. Immediately remove overspray with soap and water.
- Safety Precautions
 - Avoid breathing in spray. If inhaled, move to fresh air.
 - Avoid contact with eyes. If splashed into eyes, rinse with clean water for 15 minutes.
 - If skin irritation occurs, wash area with soap and water.
 - If accidentally ingested, immediately drink 2 glasses of water and contact a physician. Do not induce vomiting.



Manufactured by U-C Coatings, LLC
P.O. Box 1066 | Buffalo, NY 14215 | USA
(716) 833-9366 | sales@seal-once.com | www.seal-once.com

"SEAL-ONCE" and "SEAL ENDS ONCE" are registered trademarks of U-C Coatings, LLC.